

Technical Data

LayFlat Pipe >



DESCRIPTION:

- Anti-twist
- Easy to rewind for subsequent use
- Better fitting and pipe grip due to the use of braided wires ensuring steadiness on the whole length of the pipe
- 3-parts polyester wire
- Both pipe and coating are simultaneously extruded in order to obtain maximum fusion
- Working temperature: -20°C ÷ +76° C (higher than +43°C working pressure decreases)

SUN-FLOW

SF10 BLUE LAYFLAT




Ø	Code	Ø _{int} mm	Thick. mm	Press. bar exercise	mt coils
2"	TMN501	53,1	1,5	5.50	100
2½"	TMN502	65,0	1,5	4.50	100
3"	TMN503	78,0	1,6	5.50	100
4"	TMN504	104,9	1,7	4.80	100
5"	TMN505	128,0	1,8	2.76	100
6"	TMN506	156,5	1,9	4.14	100
8"	TMN508	207,0	2,2	2.41	100

SF55 GREY LAYFLAT



Ø	Code	Ø _{int} mm	Thick. mm	Press. bar exercise	mt coils
2"	TMN550	52,8	2,2	10.34	100
3"	TMN552	78,0	2,5	10.34	100
4"	TMN553	104,9	2,9	6.89	100
5"	TMN554	128,8	3,3	6.89	100
6"	TMN555	154,9	3,7	6.89	100

SF20 GREEN LAYFLAT*



Ø	Code	Ø _{int} mm	Thick. mm	Press. bar exercise	mt coils
3"	TMN603	78,0	3,0	12	91
4"	TMN604	104,0	4,0	12	91
6"	TMN605	154,0	5,0	12	91

*While stocks last

BLUE TD-FLAT



Ø	Code	Ø _{int} mm	Thick. mm	Press. bar exercise	mt coils
2"	TMN620	53,0	1,25	4,0	100
2½"	TMN622	65,0	1,50	6,0	100
3"	TMN623	78,0	1,40	3,0	100
4"	TMN624	105,0	1,40	3,0	100
5"	TMN625	128,0	1,75	3,0	100
6"	TMN626	156,5	2,00	3,0	100
8"	TMN627	207,0	2,30	2,5	100

GREEN TN-FLAT



Ø	Code	Ø _{int} mm	Thick. mm	Press. bar exercise	mt coils
2"	TMN630	53,0	1,70	10	100
2½"	TMN631	65,0	1,75	10	100
3"	TMN632	78,0	1,90	6	100
4"	TMN633	105,0	2,00	6	100
5"	TMN634	128,0	2,30	6	100
6"	TMN635	156,5	2,40	6	100

RED TR-FLAT



Ø	Code	Ø _{int} mm	Thick. mm	Press. bar exercise	mt coils
2½"	TMN640	65,0	2,30	16	100
3"	TMN641	78,0	2,35	16	100



SCARABELLI GREENFLAT



Ø	Code	Ø _{int} mm	Thick. mm	Press. bar exercise	mt coils
2"	TMN862	53	1,4	6,5	100
4"	TMN864	103	1,6	4	100
5"	TMN865	128	1,8	4	100





Technical Data

LayFlat Pipe >

Blue Pre-Holed TD-FLAT Pipe >

Recommended dripline start fittings:
for tape: RMP639 - RMP640 - RMP641 - RMP642
for dripline: RMP631 - RMP632 - RMP637 - RMP638



PRE-HOLED BLU TD-FLAT LAYFLAT PRE-INSERTED STARTER 1/2" F - ROLLS 100 MT

Øint mm	Thick. ~ mm	Ø	Departure distance				
			70 cm	90 cm	100 cm	140 cm	150 cm
			Code	Code	Code	Code	Code
53,0	1,25	2"	TMN2P07S	TMN2P09S	TMN2P10S	TMN2P14S	TMN2P15S
78,0	1,40	3"	TMN3P07S	TMN3P09S	TMN3P10S	TMN3P14S	TMN3P15S
105,0	1,40	4"	TMN4P07S	TMN4P09S	TMN4P10S	TMN4P14S	TMN4P15S
128,0	1,75	5"	TMN5P07S	TMN5P09S	TMN5P10S	TMN5P14S	TMN5P15S
156,5	2,00	6"	TMN6P07S	TMN6P09S	TMN6P10S	TMN6P14S	TMN6P15S
207,0	2,20	8"	TMN8P07S	TMN8P09S	TMN8P10S	TMN8P14S	TMN8P15S

Other spacings on request

AccessoriES

Code	Description		Code	Description	
OAF317	Torx wrench - 0 10 mm		RLF012-S	Lay-Flat 1/2" F x pre-drilled start	



Piping